

Special Lipseals

SOA Series

TECHNICAL FEATURES



	-	~													
			e outside er	6	The support ring of							Medium pressure			
		The Lin	The Lipseal must		the lipseal is made from bearing bronze and acts as							lip seal:			
		be fixat	ted against n pressure				bearing if the shaft touches the seal housing					SOA			
D1	D2	В	D1	D2	В	D1	D2	В	D1	D2	В	D1	D2	в	
5	16	5	17	30	5	30	50	5	55	70	6	95	120	7	
6	22	5		32 35			52 62	6		72 80		100	125 120	7	
6	16 22	5		35 40		32	45	5		80		100	120	'	
7	16	5	18	30	5		47	Ĩ	56	70	6		130		
	22			32			52	6		72		105	130	7	
8	16	5		35		35	47	5		80			140		
	22 24		20	40 30	5		50 52	6	58	85 72	6	110	130 140	7	
9	24	5	20	32	5		62	0	50	80	0	115	140	7	
•	24	-		35		36	47	5	60	75	6		150		
	26			40			50			80		120	150	7	
10	22	5		47			52	6		85			160		
	24		22	32	5	20	62		62	90		130	160	7	
11	26 22	5		35 40		38	52 55	6	62	85 90	6	135	170 170	7	
	24	J		47			62		63	85	6	140	170	-	
	26		24	35	5	40	52	6		90	-	145	175		
12	22	5		37			55		65	85	6	150	180		
	24			40			62			90		160	190		
	26 28		25	47 35	5	42	72 55	6	68	100 90	6	170 180	200 210		
	20 30		25	40	5	42	62	0	00	100	0	190	210	8	
14	24	5		42			72		70	90	6	200	230	<u> </u>	
	28			47		45	60	6		100		210	240		
	30			52	6		62		72	95	6	220	250		
15	35	F	26	37	5		65 72		75	100		230	260	0	
15	26 30	5		42 47		48	72 62	6	75	95 100	6	240 250	270 280	9	
	32		28	40	5	40	72	۲	78	100	6	260	300	10	
	35			47		50	65	6	80	100	6	280	320		
16	28	5		52	6		68			110	7	300	340		
	30		30	40	5		72		85	110	7	320	360		
	32 35			42 45		52	80 68	6	90	120 110	7	340 360	380 400		
17	28	5		45 47		52	72	°	30	120	'	380	400		
		~											0		

duff-france@duffnorton.fr - www.duffnorton.fr - Tel. 33 (0) 3 23 70 70 00 - Fax 33 (0) 3 23 70 70 10